

MacSema's ButtonMemory® Technology



Physical Sizes



MicroButton



MiniButton



MegaButton

What is ButtonMemory?

MacSema's Contact Memory Button (CMB) a battery-free, read/write electronic data storage tag designed for survival in extreme environments including military, aerospace, utility, transportation and industrial applications. CMBs store up to 4GB of any type of data to enhance configuration, inspection and maintenance management for the life of the asset the CMB is attached to. Data is retrieved and updated by contact using a ButtonLink probe. CMB technology eliminates time and inconvenience associated with accessing a central database. Information is viewable and updateable on site. Survive hostile conditions such as temperature extremes, radiation, ESD, EMI, EMP, shock and vibration. Each CMB has a unique serial number. Exceeds Mil-Std - 810F.

Specifications:

	Micro	Mini	Mega
Memory Size (Bytes)	4KB, 8KB (read/write)	128B, 256B 2KB, 8KB, 32KB, 64KB (read/write)	8MB, 4GB (read/write)
• Weight	0.006 ounces 0.17 grams	0.027 ounces 0.77 grams	0.18 ounces 5.0 grams
• Dimensions			
Height:	2.11 mm (0.083 in.)	2.8 mm (.11 in.)	5.1 mm (0.2 in.)
Diameter:	7.56 mm (0.298 in.)	14.3 mm (0.56 in.)	28.6 mm (1.1 in.)
• Operating Temperature	-67°F to 257° (-55°C to 125°C)	-67°F to 257°F (-55°C to 125°C)	-40°F to 185°F (-40°C to 85°C)
• Storage Temperature*	-85°F to 302°F (-65°C to 150°C)	-85°F to 302°F (-65°C to 150°C)	-85°F to 302°F (-65°C to 150°C)
* CMBs can survive temperature extremes and are actually used in applications at storage temperatures approaching 392°F (200°C). Contact MacSema to discuss your specific requirements.			
• Interface	USB RS-232 Serial	USB RS-232 Serial	USB
• Read Rate (USB)	31KB/second	31KB/second	1MB/second
• Casing	Brass. Components encapsulated to withstand water, oil, dust, grease, salt, radiation, weather extremes, electromagnetic fields and mechanical stress. Also available in a black finish.		
• Power	Passive, Non-volatile memory (no battery or internal power source)		
• ESD	15kV, 20 pulses per second, human model		
• EMP	5.8, 26.7 and 55.0 kV/m		
• EMI	Classified as non-susceptible to RF signals of 200V/M		
• Audit Trail	Each read and write can be date and time stamped		
• Radiation	Immune to 100 Krad of 60 Co gamma irradiation		
• Humidity	100% RH - CMB can be submerged		
• Life Expectancy	Unlimited Reads. More than 1,000,000 write cycles. Data Retention greater than 100 years; refresh every 35 years		

A summary of DOD environmental test results is available

MacSema, Inc.

62971 Plateau Drive, Suite 400 • Bend, OR. USA 97701-5874

Phone (541) 389-1122 • Fax (541) 389-1888

e-mail: sales@macsema.com

www.macsema.com